



China 6204 Bearing Supplier



6002 Bearing 2D drawings and 3D CAD models

High Security and High Performance Deep Groove Ball Bearing KOYO 6002 Bearing Price

Bearing No. 6002

| | |
|-------------------------------|--------------------------|
| Size | 15x32x9 mm |
| Bore Diameter | 15 mm |
| Outer Diameter | 32 mm |
| Width | 9 mm |
| d | 15 mm |
| D | 32 mm |
| B | 9 mm |
| C | 9 mm |
| r min. | 0,3 mm |
| da min. | 17 mm |
| Da max. | 30 mm |
| ra max. | 0,3 mm |
| Weight | 0,03 Kg |
| Basic dynamic load rating (C) | 5,6 kN |
| Basic static load rating (C0) | 2,85 kN |
| (Grease) Lubrication Speed | 23000 r/min |
| (Oil) Lubrication Speed | 27000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.033 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |



China 6204 Bearing Supplier

| | |
|---------------------------------|---|
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 15MM Bore; 32MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.koyousa.com |
| Manufacturer Item Number | 6002 |
| Weight / LBS | 0.073 |
| Bore | 0.591 Inch 15 Millimeter |
| Outside Diameter | 1.26 Inch 32 Millimeter |
| Outer Race Width | 0.354 Inch 9 Millimeter |
| Bearing No. | 6002 |
| r(min) | 0.3 |
| Cr | 7.00 |
| C0r | 2.85 |
| Cu | 0.150 |
| f0 | 13.9 |
| Grease lub. | 23000 |
| Oil lub. | 27000 |
| | |



China 6204 Bearing Supplier

| | |
|------------------|-------|
| da(min) | 17 |
| Da(max) | 30 |
| ra(max) | 0.3 |
| (Refer.)Mass(kg) | 0.030 |